



# BONA CARL'S 90

## Product Description

### Features

Carl's 90 is a hardening tall oil containing less than 10% solvents which is intended for the surface treatment of untreated wooden floors exposed to normal or heavy wear. Due to its easy application and quick drying, the floor may be completed within one working day.

- Based on tall oil from pine trees
- Dry solids 90%
- Easy to apply
- Dries quickly
- Ready in a day
- Practically no bleed-back
- Excellent coverage rate
- Meets RAL-UZ 38 for VOC and formaldehyde emissions
- Meets DIN EN 71/3 for use on children's toys

### Technical Data

Type of oil:	Esterified tall oil
Solids content:	Approx. 90 %
Density:	0.92 kg/dm <sup>3</sup>
Dilution:	Do not dilute
Waiting time between applications:	Approx. 20 minutes
Application tool:	Solvent-resistant rubber applicator
Total consumption:	Approx. 10-12 m <sup>2</sup> /litre depending on type of wood
Safety:	Unclassified
Fire risk:	Yes (see the Safety Data Sheet)
Flash point:	56°C
Shelf life:	At least 2 years, from the date of production, in unopened original container
Storage:	Store frost-free
Pack size:	2 x 5 litres (35 boxes per pallet) 6 x 1 litre (72 boxes per pallet)