



# BONA SPECTRA

## Product Description

### Features

Spectra is a one-component waterborne polyurethane/acrylate finish for the surface treatment of wooden floors in homes and other areas subject to normal wear. The high viscosity provides a well-bodied surface and makes application easy without affecting the good levelling properties. Also, Spectra does not cause any yellow discolouration.

- Designed for use primarily in the domestic area
- Based on a special polyurethane/acrylate co-polymer dispersion
- High viscosity but still good levelling
- Well-bodied surface
- Resistant to light – non-yellowing
- Good scuff resistance
- Good resistance to wear
- Good chemical resistance

### Technical Data

Type of finish:	1-comp. waterborne PU/acrylate co-polymer
Solids content:	Approx. 32%
Viscosity:	Approx. 20 sec. (25°C, FC4)
pH-value:	Approx. 8
Resistance to wear:	Approx. 5 mg/100 revolutions (SIS 923509)
Density:	1.05 kg/dm <sup>3</sup>
Sheen (at 60°):	Gloss: approx. 90, Silk matt: 45-50, Matt: 25-30
Mixing ratio:	The finish is 1-component
Drying time:	2-3 hours at 20°C / 60% R.H.
Application tools:	Roller
Application rate:	8-10 m <sup>2</sup> /litre (100-120g/m <sup>2</sup> ) per coat
Safety:	Unclassified
Flash point:	Non-flammable
Shelf life:	At least 1 year, from the date of production, in unopened original container
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Pack size:	3 x 5 litres (44 boxes per pallet) 10 x 1 litre (50 boxes per pallet)

