



BONA MEGA

Product Description

Features

Mega is a one-component waterborne 100% polyurethane finish for the surface treatment of wooden floors in commercial and domestic areas subject to heavy wear. As crosslinking is achieved using the oxygen in the air, Mega has the performance of a two-component finish without requiring any mixing. It has all the advantages of a waterborne system and has a solvent content of approx. 5%.

- Easy to use – one component with userfriendly properties.
- High resistance to wear, scuff marks and scratches
- Very good chemical resistance

Technical Data

Type of finish:	1-component waterborne 100% polyurethane oxygen crosslinking finish
Solids content:	Approx. 32%
Viscosity:	Approx. 17 sec. (25°C, FC4)
pH-value:	Approx. 7.8
Resistance to wear:	Approx. 5 mg/100 revolutions (SIS 923509)
Sheen (at 60°):	Gloss: approx. 90, Silk Matt: 45-50, Matt: 25-30
Mixing ratio:	The finish is 1-component
Drying time:	2½-3 hours at 20°C / 60% R.H.
Application tools:	Roller, lacquer brush or applicator
Application rate:	8-10 m ² /litre (120-100g/m ²) per coat
Safety:	Unclassified
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 5 litres (44 boxes per pallet) 10 x 1 litre (50 boxes per pallet)